



Key Features

- Infrared Communication Port for quick and convenient wireless connectivity
- Advanced Integration Capabilities fit seamlessly into most integrated entertainment solutions
- Infrared Input Port: For use with IR keypads and repeater systems
- Unique IR Code Sets Allow up to 12 units to be operated independently within 1 IR repeater system
- Attractive Silver Metallic Finish

Additional Features

General Features

- 2-channel Amplifier For use with multi-room systems and A/V receivers
- Volume and Mute Control Using IR Eliminates need for an external volume control
- 12V Trigger Input For activation by other devices
- 12V Trigger Output with Delay Powers multiple amps without tripping circuit breakers with 1.5 second delay
- Audio Signal Sensor Automatically activates power when audio signal is detected
- Discrete Power On and Off For use with macro-driven controllers
- Back Panel IR Code Generator Enables simple IR code learning directly from device
- Gain Controls Allows balancing of source output with amplifier output, easily accessible by installer behind front knockout panel
- 19-inch Rack Mountable For easy installation, rack-mount hardware supplied
- 5 Year Parts & Labor Limited Warranty backed by Sony quality and dependability
- 35W x 2: 8 ohms 20Hz-20kHz, THD 0.09%
- 40W x 2: 4 ohms 20Hz-20kHz, THD 0.09%

Features

General

- Silver Finish Distributed Audio Amplifier
- 35W x 2 (8 ohms 20Hz-20kHz, THD 0.09%)
- 40W x 2 (4 ohms 20Hz-20kHz, THD 0.09%)
- Audio Signal Sensor Activation
- 19-inch Rack Mountable

IR Programming

- 12 Distinct IR Code Sets
- IR Programming from Back Panel
- Vol +/- and Mute On/Off (Toggle)

Inputs and Outputs

- 12V Trigger In x 1
- 12V Trigger Out With 1.5 sec Delay x 1
- IR Input Port with Pass-Through x 1
- IR Output Port x 1

Specifications

General

- Power Consumption: 100W
- Power Requirements: 120V, 60Hz
- Frequency Response: 5-100Khz, +0.5/-2dB
- Residual Noise: <150_V or less
- Channel Separation: 60dB/45dB

Audio Input

- Sensitivity: 150mV
- Impedance: 50kilo Ohms
- S/N: 94dB (A-weighted filter, 150mV input level)

Audio Output

- Voltage: Minimum 2V without clipped
- Impedance: 1 kilo Ohms
- S/N: 102dB (A-weighted filter, 2V output)

Supplied Accessories

- Instruction Manual
- AC Power Cord x 1
- Rack Mount Ear x 2
- Rack Mount Screw x 8

Weights and Measures

- 14 lbs. 5 oz (6.5 kg)
- 17" x 2 5/8" x 13 7/8" (430 x 67 x 350 mm)

UPC Code

- TBD

SONY®

Sony Electronics Inc.
1 Sony Drive
Park Ridge, NJ 07656

For more information:

<http://www.sony.com/dn>